

# Stainless steel platform scale KERN SFB



## Stainless steel platform scale with IP65, XL platform and EC type approval [M]

### Features

- **Ideal for the robust industry.** Robust version, easy to clean. Suitable for the ever-increasing hygienic requirements in the food industry
- Scale entirely out of stainless steel
- **Load cell stainless steel**, silicone-coated. Note: Silicone is not suitable for contact with aggressive substances such as acids etc. or for continuous use in wet areas
- **Flexible positioning of display device:** eg. free-standing or mounted to the wall
- Superior display size: digit height 52 mm. Bright backlight for easy reading of weight, even in poor lighting conditions
- **Level indicator and foot screws** to level the balance precisely, fitted as standard, to give

- the most accurate weighing results
- Supports you in your HACCP-compliant quality system

### Technical data

- Large backlit LCD display, digit height 52 mm
- Dimensions of weighing plate (stainless steel) WxDxH **A** 500x400x137 mm, see larger picture **B** 650x500x142 mm
- Dimensions of display device WxDxH 266x165x96 mm
- Cable length of display device approx. 2,5 m
- Rechargeable battery pack internal, standard, operating time approx. 80 h, charging time approx. 12 h
- Permissible ambient temperature 0 °C / 40 °C, KERN SFB-M: -10 °C / 40 °C

### Accessories

- **Data interface RS-232**, interface cable included, approx. 1.5 m, must be ordered at purchase, KERN KFN-A01
- **Stand** to elevate display device, height of stand approx. 600 mm, KERN SFB-A01
- **Suitable printers** see page 138

### STANDARD



### OPTION



### FACTORY






































Model	Weighing range [Max] kg	Readout [d] g	Verific. value [e] g	Minimum load [Min] g	Net weight approx. kg	Weighing plate	Options			
							Verification		DKD Calibr. Certificate	
							M III	KERN	DKD	KERN
SFB 50K-3XL	50	5	-	-	15	A	-	-	963-128	
SFB 100K-2L	100	10	-	-	15	A	-	-	963-129	
SFB 100K-2XL	100	10	-	-	24,5	B	-	-	963-129	
SFB 200K-2XL	200	20	-	-	24,5	B	-	-	963-129	

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

SFB 60K-2XLM	60	20	20	400	15	A	965-229		963-129	
SFB 100K-2MLM	150	50	50	1000	15	A	965-229		963-129	
SFB 100K-2XLM	150	50	50	1000	24,5	B	965-229		963-129	
SFB 300K-1LM	300	100	100	2000	24,5	B	965-229		963-129	

# KERN Pictograms

 <b>Internal adjusting (CAL):</b> Quick setting of the balance's accuracy with internal adjusting weight (motordriven).	 <b>Recipe level A:</b> Separate memory for the weight of the tare container and the recipe ingredients (net total).	 <b>Rechargeable battery pack:</b> rechargeable set.
 <b>Adjusting program (CAL):</b> For quick setting of the balance's accuracy. External adjusting weight required.	 <b>Recipe level B:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.	 <b>Mains adapter:</b> 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.
 <b>Memory:</b> Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.	 <b>Recipe level C:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as barcode and back calculation functions.	 <b>Power supply:</b> integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.
 <b>Data interface RS-232:</b> To connect the balance to a printer, PC or network.		 <b>Strain gauges:</b> Electrical resistor on an elastic deforming body.
 <b>RS 485 data interface:</b> To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.	 <b>Percentage determination:</b> Determining the deviation in % from the target value (100%).	 <b>Tuning fork principle:</b> A resonating body is electromagnetically excited, causing it to oscillate.
 <b>USB data interface:</b> To connect the balance to a printer, PC or other peripheral devices.	 <b>Weighing units:</b> Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 <b>Electromagnetic force compensation:</b> Coil in a permanent magnet. For the most accurate weighings.
 <b>Bluetooth data interface:</b> To transfer data from the balance to a printer, PC or other peripheral devices.	 <b>Weighing with tolerance range:</b> Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.	 <b>Single cell technology:</b> Advanced version of the force compensation principle with the highest level of precision.
 <b>Control outputs (optocoupler, digital I/O):</b> to connect relays, signal lamps, valves, etc.	 <b>Vibration-free weighing:</b> (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.	 <b>Verification possible:</b> The time required for verification is specified in the pictogram.
 <b>Interface for second balance:</b> for direct connection of a second balance.	 <b>Spray and dust protection IPxx:</b> The type of protection is shown by the pictogram. For details see the glossary.	 <b>DKD calibration possible:</b> The time required for DKD calibration is shown in days in the pictogram.
 <b>Network interface:</b> For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.	 <b>Stainless steel:</b> the balance is protected against corrosion.	 <b>Package shipment:</b> The time required to manufacture the product internally is shown in days in the pictogram.
 <b>GLP/ISO record keeping:</b> of weighing data with date, time and identification-no. Only with printers from KERN.	 <b>Suspended weighing:</b> load support with hook on the underside of the balance.	 <b>Pallet shipment:</b> The time required to manufacture the product internally is shown in days in the pictogram.
 <b>Piece counting:</b> Reference quantities selectable. Display can be switched from piece to weight.	 <b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device.	 <b>Warranty:</b> The warranty period is shown in the pictogram.

## Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of its accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.

(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

### Range of services:

- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages  
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

## Your KERN specialist dealer: