

Hanging scales **KERN HCB · HCN**

Practical assistant for the mobile weighing of heavy house pets, animal feed etc. up to 1 t!



KERN HCB



KERN HCB 0.5T-3



KERN HCN
Housing stainless steel, IP65:
Protected against dust and
water splashes

Your KERN specialist dealer:



Features

- Thanks to the animal weighing function, it can also be used by vets. Compact so it can be stored in the vet's case and is ideally suited for heavy domestic animals
- Data hold function: For easy reading of the weight, the display can be „frozen“ in different ways. Either automatically when the weighing value remains unchanged or manually by pressing the Hold key
- Varied options for hanging the items, thanks to the stainless steel hook and stainless steel snap links included as standard
- Peak load display (peak hold), measuring frequency 5 Hz
- Large LCD display, digit height 12 mm

HCN

- Ready for use: Batteries included (2 x 1.5 V AA), operating time approx. 200 h
- Housing stainless steel, IP65: Protected against dust and water splashes
- Second display on the rear of the balance

Accessories for models with [Max] ≤ 200 kg

- Hook (stainless steel) standard, aperture approx. 25 mm, can be reordered, **KERN HCB-A02**
- Snap link (stainless steel) with safety catch standard, aperture approx. 15 mm, can be reordered, **KERN HCB-A01**

HCB

- Ready for use: Batteries standard, 3 x 1.5 V AA, operating time approx. 300 h
- HCB with [Max] ≥ 0,5 t: Reinforced versions for heavy loads. Snap link and hook not included

STANDARD



OPTION



Model	Weighing range [Max] kg	Readout [d] g	LCD display, digit height mm	Dimensions housing WxDxH mm	Height with snap link and hook mm	Net weight approx. kg	Option	
							DKD KERN	DKD Calibr. Certificate
KERN								
HCB 20K10	20	10	12	80x45x150	290	0,4	963-128	
HCB 20K50*	20	50	12	80x45x150	290	0,4	963-128	
HCB 50K20	50	20	12	80x45x150	290	0,4	963-128	
HCB 50K100	50	100	12	80x45x150	290	0,4	963-128	
HCB 99K50	99	50	12	80x45x150	290	0,4	963-129	
HCB 100K200	100	200	12	80x45x150	290	0,4	963-129	
HCB 200K100	200	100	12	80x45x150	290	0,4	963-129	
HCB 200K500	200	500	12	80x45x150	290	0,4	963-129	
HCB 0.5T-3	500	1000	12	84x42.5x152	-	0,35	963-130	
HCB 1T-3	1000	2000	12	80x48x150	-	0,52	963-130	
stainless steel								
HCN 20K50IP	20	50	12	95x55x175	315	0,8	963-128	
HCN 50K100IP	50	100	12	95x55x175	315	0,8	963-128	
HCN 100K200IP	100	200	12	95x55x175	315	0,8	963-129	
HCN 200K500IP	200	500	12	95x55x175	315	0,8	963-129	

* ONLY WHILE STOCKS LAST

New model

Pictograms:



Adjusting program (CAL):
For quick setting of the balance's accuracy. External adjusting weight required.



Weighing units: Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.



Spray and dust protection IPxx:
The type of protection is shown by the pictogram. For details see the glossary.



Stainless steel:
the balance is protected against corrosion.



Animal weighing program:
Vibrations are filtered out so that a stable weight is obtained.



Battery operation:
Ready for battery operation. The battery type is specified for each device.



Package shipment:
The time required to manufacture the product internally is shown in days in the pictogram.



Warranty:
The warranty period is shown in the pictogram.



DKD calibration possible:
The time required for DKD calibration is shown in days in the pictogram.