



# 368 Close-Focus, Pocket Size Infrared Thermometer

**Instantly read surface temperatures.**

## IR APPLICATIONS

### HVACR

- Compressor heads
- Vents
- Leaks around cooler or freezer doors
- Leaks around windows
- Steam traps
- Registers

### FOOD

- Surface temperatures
- Holding cabinets
- Serving temperatures
- Storage temperatures

### ELECTRICAL

- Cables
- Circuit breakers
- Connections
- Machinery
- Motors & Transformers

Turn over for technical information and accessory part numbers.

**The Value Leader™**

**3-YEAR LIMITED WARRANTY**



*removeable wrist strap*

**1.5" W x 2.75" H**

**Actual Size**

## Features

- Close focus 1/8" ~ 1.5"
- Selectable Fahrenheit of Centigrade temperature range: 7° to 248°F or -22° to 120°C
- Compact - Easily fits in your pocket
- Auto Data Hold: Point the unit at the surface to be measured then press and hold down the ON/SET button. Temperature will be displayed in less than 2 seconds and held on the display for 10 seconds.
- Min/Max functions displays the minimum or maximum temperature of 8 samplings in 0.5 seconds.
- AUTO sets the 368 into scan mode to continuously scan surface temperatures in real time. Automatically powers off after 60 minutes.
- NOTE: Close-focus IR thermometers should be held a distance .5 to 2 inches from surface to be measured to obtain an accurate reading (spot size 0.35")



# 368 Close-Focus Pocket-Size IR Thermometer

## SPECIFICATIONS

### TECHNICAL SPECIFICATIONS AND ACCESSORIES

- Digital Multimeters
- Clamp Meters
- Hand-held Oscilloscopes
- Refrigerant & Combustible Gas Leak Detectors
- Temperature Testers
- BNC Coax Cable Connectors
- Test Leads
- Accessories

#### Test Products

##### International, Inc.

Headquarters:  
9615 SW Allen Blvd.  
Beaverton, OR 97005  
USA  
503-520-9197  
Fax: 503-520-1225  
email:  
info@tpi-thevalueleader.com

#### Test Products

##### International, Ltd.

342 Bronte St. South  
Unit 9  
Milton, Ontario L9T  
5B7  
Canada  
905-693-8558  
Fax: 905-693-0888  
email:  
info@tpicanada.com

#### Test Products

##### International UK Ltd.

Longley House, East Park  
Crawley, West Sussex  
RH10 6AP England  
Tel: +44 (0)1293 561212  
Fax: +44 (0)1293813465  
contactus@tpieurope.com

Range	-7° to 248°F or -22° to 120°C
Operating temp	32° to 104°F or 0° to 40°C
Accuracy	2% of reading or ±3.5%, whichever is greater
Response Time	Less than 0.5 second
Resolution	0.1°F/C
Emmissivity	0.95 fixed
Distant to Spot Ratio	1:1.3
Battery	A003
Battery Life	50 hours continuous use, auto off after 10 sec.

**THIS INSTRUMENT** is in compliance with EN50 081-1:1992, EN 50 082-1:1992, IEC 801-2:1984, IEC 801-3:1984, IEC 801-4:1998

### *Distributed By:*



To learn about the entire line of TPI products visit:

**www.tpi-thevalueleader.com**

L 368-0804

Copyright © 2004 Test Products International, Inc.