



EN 61010-1
EN 61010-2-032
EN 61326-1



■ UT255A

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT255A	UT255B
Model		UT255A	UT255B
Leakage Current(A)	0.01mA~100.0A	±(1%+5)	±(1%+5)
	100.0A~600.0A	±(2%+5)	±(2%+5)
	Voltage(Freq.) 0V~69kV(50Hz/60Hz)	√	√
Display Mode	4 Digits Display LCD	√	√
Jaw Capacity		33mm	33mm
Auto Range		√	√
Wireless Transmission	≤30m		√
Data Storage		99	99
Data Recall		√	√
Peak Value		√	√
LCD Backlight		√	√
Data Hold		√	√
Auto Power Off	Around 15 Minutes	√	√
Low Battery Indication		√	√
Over-Range Display	OL	√	√
Test Mode	Clamp CT, Integral Approach	√	√
Sample Rate	About 2 times/second	√	√



■ UT255B

GENERAL CHARACTERISTICS

Power	1.5V Batteries(LR03) × 4
LCD Size	47mm × 28.5mm
Product Color	Red and Grey
Product Net Weight	335 g
Product Size	68mm × 245mm × 40mm
Standard Accessories	UT255A -Batteries,Insulation Rod , Tool Box UT255B -Batteries,Insulation Rod,Receiver,Tool Box
Standard Individual Packing	Gift Box, Tool Box, English Manual
Standard Quantity Per Carton	1 PCs
Standard Carton Measurement	1040mm × 240mm × 140mm (0.05CBM Per Standard Carton)
Standard Carton Gross Weight	6.8 Kg