

MIT2500

CAT IV Insulation testers



- **Insulation testing up to 2.5 kV (New) and 200 GΩ range in a hand held instrument**
- **Guard terminal for high resistance accuracy (New)**
- **Adjustable insulation test voltage from 50 V to 2500 V (New)**
- **Stabilised insulation test voltage (New)**
- **Rechargeable options for mains and car charging (New)**
- **Single range, faster continuity testing from 0.01 Ω to 1 MΩ (New)**
- **Polarisation Index (PI) & Dielectric Absorption Ratio (DAR)**
- **CAT IV 600 V applications**

DESCRIPTION

The MIT2500 insulation and continuity tester has been designed for Electrical and Industrial test applications, where operation voltages exceed 1000 V and higher insulation test voltages are needed.

The MIT2500 offers both fixed range voltages of 50 V, 100V, 250 V, 500 V, 1000 V and 2500 V, as well as a variable range that allows any voltage between 50 V and 2500 V to be "dialed in". This is supported by the new test voltage feedback control, which maintains the output test voltage to within 2% of the selected range, even when under test.

The MIT2500 uses the redesigned case, back-stand, and 6 cell battery compartment, as well as incorporating a Guard terminal to reduce surface tracking currents that reduce accuracy at higher voltages.

All instruments are over-moulded for increased protection and achieve an IP54 weatherproof rating

INSULATION RESISTANCE TESTING

The feedback controlled insulation test voltage is now accurate to +2% -0% compared to the original +20%, providing a more accurate test voltage without the risk of over-voltage damage to circuits.

A variable range allows the exact test voltage to be selected from 50 V to 999 V in 1 V steps, (1KV to 2.5KV in 10 V steps) providing 1100 test voltage options.

FEATURES INCLUDE:

- **Test voltages (New)**
 - 50 V, 100 V, 250 V, 500 V, 1000 V, and 2500 V
- **Guard terminal**
 - Improved performance on higher insulation test ranges
- **2.5 kV Silicone test leads (New)**
 - Purpose designed high 2.5 kV silicone test leads are included as well as standard 1000 V CAT III / 600 V CAT IV general purpose test leads.
- **Variable test voltage (New)**
 - Adjustable test voltage from 50 V to 999 V in 1 V steps, 1000 V to 2500 V in 10 V steps
- **2% Test voltage accuracy**
 - The output test voltage is maintained within the tolerance of -0% +2% +2 V
- **Stabilised test voltage**
 - The voltage is feedback controlled to ensure it remains within specification throughout the full test range
- **Test voltage display (New)**
 - The actual test voltage is displayed on the smaller digital readout, with the measurement on the larger digital display.
- **Measurement range displayed**
 - The range voltage is displayed during selection.
- **Measurement voltage display (New)**
 - The measurement voltage is displayed during the test.
- **Analogue arc**
 - The display also features an analogue arc to replicate the response of a moving coil display.
- **PI and DAR**
 - Automatic Polarisation Index (PI) and Dielectric Absorption Ratio (DAR) functions. Polarisation Index (PI): 10 min / 1 minute ratio
Dielectric Absorption Ratio (DAR): 60 sec / 30 sec ratio

- **Timed testing**
 - Automatically test to a time limit.
- **200 GΩ range**
 - Insulation testing up to 200 GΩ at ≥1000 V.
- **Test inhibit**
 - prevents testing if voltages in excess of 25, 30, 50, 75 or 100 V (set by the user) are detected when making insulation tests. Default is 50 V.
- **Insulation buzzer**
 - The buzzer can be set to sound if the insulation resistance is above a user adjustable limit, configurable in the Setup menu.
- **Test Lock**
 - Holds insulation test on continuously.

Test ranges extend from 10 GΩ to 200 GΩ depending on test voltage as below:

| | |
|--------------|--------|
| ■ 50 Volts | 10 GΩ |
| ■ 100 Volts | 20 GΩ |
| ■ 250 Volts | 50 GΩ |
| ■ 500 Volts | 100 GΩ |
| ■ 1000 Volts | 200 GΩ |
| ■ 2500 Volts | 200 GΩ |

The MIT2500 also includes a Guard terminal to prevent errors from stray leakage paths.

VARIABLE INSULATION VOLTAGE (NEW)*

The variable mode provides a unique solution for awkward insulation voltage measurement applications. The range option allows an insulation test voltage from 50 V to 999 V in 1 V steps, 1.0 KV to 2.5 KV in 10 V steps.

TYPICAL APPLICATIONS INCLUDE

- Commercial Avionics
- Military Land, Marine and Air communications
- Manufacturing/production line goods
- Electrostatic measurement
- Component testing
- Battery powered traction and lifting equipment

GUARD TERMINAL

The Guard terminal (G) is a third terminal on the connection panel. Connection of the guard terminal on certain applications provides a return path for parallel leakage currents that could otherwise create significant errors in the insulation measurement. This is especially so for surface contamination of equipment or cables.

- For voltages of 1000 V and above, or expected insulation values over 100 MΩ the guard terminal should be considered to reduce measurement error.

CONTINUITY (RESISTANCE) TESTING

- **Single resistance range (New)**
 - One range fully automatic from 0.01 Ω to 1.0 MΩ.
- **Auto test current selection**
 - Automatically uses the preferred test current for the load resistance under test.
- **Bi-directional testing (New)**
 - Option for automatic bi-directional testing without reconnecting leads.
- **Fast response time (New)**
 - Response time on contact buzzer has been reduced
- **200 mA or 20 mA**
 - Either 200 mA or 20 mA continuity test currents are available. 20 mA test current will considerably increase battery life.
- **Lead null**
 - Lead resistance compensation (NULL) operates up to 10 Ω of resistance.
- **Buzzer - ON/OFF** selected by simple push button.
- **Buzzer limit**
 - Continuity buzzer limit alarm provides adjustment of the maximum resistance the continuity buzzer sounds. This is adjustable from 1 Ω to 200 Ω in 12 steps.
- **Display PASS/FAIL (✓/✘) warnings (New)**
 - For use where buzzer indication may be disruptive.

VOLTAGE MEASUREMENT

True RMS voltage measurement to 600 V ac or dc with resolution from 0.1 mV.

- Digital voltage measurement up to 600 V ac/dc
- Automatic display of frequency during voltage measurement.

DISPLAY

The display offers a combination of Analogue arc and a dual digital readout:

Analogue arc:

- Full display width analogue arc.
- Arc display shows essential charge and discharge characteristics not visible on a digital display.
- Single pointer "needle" response has a similar response to a moving coil meter.

Dual digital display

- Large main digital readout for good visibility of all main measurement results
- Second digital display for additional data such as:
 - Insulation test voltage.
 - Insulation leakage current.
 - Supply frequency (when measuring volts).
 - Test mode eg. PI, DAR or t (t = Timer mode).

OTHER FUNCTIONS AND FEATURES

Setup functions:

Allow control of:

- Continuity buzzer limit alarms,
- Insulation buzzer limit alarms,
- Insulation LOCK
- Insulation test timer duration
- Backlight ON duration
- Sleep timer
- Continuity test currents,
- Factory reset

Weatherproof:

Every tester is sealed to IP54, providing a weatherproof case to reduce the chances of water ingress, including the battery and fuse compartment.

Tough housing:

Rubber over moulding combines the tough shock absorbing outer protection with excellent grip, on a strong modified ABS housing, providing an almost indestructible case.

Batteries:

Battery requirements are 6 AA batteries of either standard Alkaline or Nickel Metal Hydride (NiMH) rechargeable type, providing a minimum of 3000 insulation tests at 1000 V.

The MIT2500 is enabled for internal charging when used with the optional charging pack.

STORAGE & DOWNLOADING RESULTS

Revised Bluetooth® and pairing procedures have made the MIT2500s far easier to pair and download data. The test results are downloaded to a CSV file which can then be opened as an Excel® spreadsheet.

SAFETY

Designed to be exceptionally safe to use, fast detecting circuitry prevents damage to the instruments if accidentally connected to live circuits or across phases. Specifically, all instruments:

- Meet the international requirements of IEC61010 and EN61557.
- Live circuit detection inhibits insulation testing on circuits above 25, 30, 50 74 or 100 V default (50 V).
- Live circuit detection and test inhibit on continuity measurements.
- Default display of live circuit voltage on all ranges.
- Detection and inhibit functions even if the protection fuse has failed.
- Suitable for use on CAT IV applications and supply voltages to 600 V.

MIT2500 INCLUDED ACCESSORIES:

Silicone test leads:

2.5 kV rated test leads fitted with medium size Croc clips
1 x Red, 1 x Black, 1 x Blue (Guard)

1 kV rated standard test leads with Probes and clips
1 x Red, 1 x Black

OPTIONAL ACCESSORIES

Battery charger:

A charging pack is available to charge the MIT2500 when fitted with NiMH AA batteries.

Remote Switch Probe

APPLICATION

- Single and three phase rotating machinery
- Single and multi-core cable testing
- Motor testing

FEATURES AND BENEFITS

- Designed for the Electrical and Industrial markets
- Insulation testing up to 2.5 kV (New) and 200 GΩ range in a hand held instrument
- Guard terminal for high resistance accuracy (New)
- Adjustable insulation test voltage from 50 V to 2500 V (New)
- Stabilised insulation test voltage (New)
- Rechargeable options for mains and car charging (New)
- Single range, faster continuity testing from 0.01 Ω to 1 MΩ (New)
- Polarisation Index (PI) & Dielectric Absorption Ratio (DAR)
- 600 V Trms AC and DC voltage measurement
- New case design with optional magnetic hanging strap (New)
- Test result storage and review and Bluetooth download
- Live circuit detection and protection
- CAT IV 600 V applications
- IP54

FUNCTIONAL SUMMARY

| | |
|---|--------|
| INSULATION | |
| 50 V / 100 V | ■ |
| 250 V / 500 V / 1000 V | ■ |
| 2500 V | ■ |
| VARIABLE voltage from 50 V to 2500 V | ■ |
| PI- / DAR / timed | ■ |
| Lock button on MΩ | ■ |
| Guard terminal | ■ |
| CONTINUITY | |
| Continuity 0.01 Ω - 1 MΩ | ■ |
| Auto reverse polarity (setup ON-OFF) | ■ |
| Lead null (<10 Ω) | ■ |
| VOLTAGE | |
| AC / DC Volts 600 V | ■ |
| mV AC / DC range | ■ |
| Frequency measurement 15 - 400 Hz | ■ |
| Input impedance | 250 kΩ |
| CAPACITANCE | |
| Capacitance 0.1 nF - 10 μF | ■ |
| OTHER FEATURES | |
| PASS/FAIL on limit alarms | ■ |
| Auto power down (setup) | ■ |
| On board memory | ■ |
| Bluetooth® Download and Software | ■ |
| AA Alkaline or NiMH | ■ |
| Recharger ready | ■ |
| CAT IV 600 V | ■ |
| ACCESSORIES | |
| Silicone leads (Red/Black/Blue with probes and clips) | ■ |
| 2.5 kV Silicone croc clip leads | ■ |
| OPTIONAL Switched probe supplied | ■ |
| OPTIONAL Battery charger available | ■ |

SPECIFICATIONS

All quoted accuracies are at +20 °C.

Insulation

Insulation accuracy

| | | | | |
|------------|--------|------|------------|---------------|
| 50 Volts | 10 GΩ | ± 2% | ± 2 digits | ± 4.0% per GΩ |
| 100 Volts | 20 GΩ | ± 2% | ± 2 digits | ± 2.0% per GΩ |
| 250 Volts | 50 GΩ | ± 2% | ± 2 digits | ± 0.8% per GΩ |
| 500 Volts | 100 GΩ | ± 2% | ± 2 digits | ± 0.4% per GΩ |
| 1000 Volts | 200 GΩ | ± 2% | ± 2 digits | ± 0.2% per GΩ |
| 2500 Volts | 200 GΩ | ± 2% | ± 2 digits | ± 0.2% per GΩ |

Service Error: BS EN 61557-2 (2007).

| | | | |
|--------|--------------|---------------|---------|
| 50V, | ± 2.0% ± 2d, | 100kΩ - 900kΩ | ± 10.5% |
| 100V, | ± 2.0% ± 2d, | 100kΩ - 900kΩ | ± 10.3% |
| 250V, | ± 2.0% ± 2d, | 100kΩ - 900kΩ | ± 10.3% |
| 500V, | ± 2.0% ± 2d, | 100kΩ - 900kΩ | ± 10.3% |
| 1000V, | ± 2.0% ± 2d, | 100kΩ - 900kΩ | ± 11.5% |

Guard terminal performance <5% error at 500 kΩ parallel circuit resistance with 100 MΩ load

Display range Analogue: 1 GΩ full scale

Resolution 0.1 kΩ

Short circuit/charge current 2 mA +0% -50% to EN 61557-2 (2007) (except 2500 V)

Terminal voltage accuracy -0% +2% ± 2V

Test current 1 mA at min. pass value of insulation to a maximum of 2 mA max

Operation EN61557 : 0.10 MΩ to 1.0 GΩ

Leakage current display 10% ±3 digits

Voltage ±3% ±2 digits ±0.5% of rated voltage

Timer control Countdown timer 60 second (adjustable to 10 minutes)

Note Above specifications only apply when high quality silicone leads are being used.

Continuity:

Continuity measurement 0.01 Ω to 1 MΩ (0 to 1000 kΩ on analogue scale)

Continuity accuracy ± 3% ± 2 digits (0 to 100 Ω)
± 5% ± 2 digits (100 Ω - 500 k Ω)
Service Error: BS EN 61557-4 (2007) - ± 2.0%, 0.1 Ω - 2 Ω ± 6.8%

Open circuit voltage 5 V ± 1 V

Test current 200 mA (-0 mA +20 mA)
(0.01 Ω to 4 Ω)

Polarity Single polarity (Default) / Dual polarity (configurable on setup).

Lead resistance Null up to 10 Ω

Voltage range:

Voltage range DC:
0 to 600 V
AC:
10 mV to 600 V TRMS sinusoidal
(15 Hz to 400 Hz)
Unspecified:
0 - 10 mV (15 to 400 Hz)

| | |
|---------------------------------------|--|
| Volt range accuracy | DC: $\pm 2\% \pm 2$ digits AC: $\pm 2\% \pm 2$ digits |
| | Service Error: BS EN 61557-1 (2007) - $\pm 2.0\% \pm 2d$, 0V - 300Vac/dc $\pm 5.1\%$ |
| Waveform | Non-sinusoidal: $\pm 3\% \pm 2$ digits >100 mV to 600 V TRMS $\pm 8\% \pm 2$ digits 10 mV to 100 mV TRMS |
| Default voltmeter | $\pm 0.5\% \pm 1$ digit (100 Hz to 400 Hz) unspecified |
| Frequency: | |
| Frequency measurement range | 15 Hz - 400 Hz |
| Frequency measurement accuracy | $\pm 0.5\% \pm 1$ digits |
| Capacitance measurement: | |
| Capacitance range | 0.1 nF to 10 μ F |
| Accuracy | $\pm 5.0\% \pm 2$ digits (1 nF-10 μ F) |
| Results storage: | |
| Storage capacity | >1000 test results |
| Data download | Bluetooth [®] wireless Bluetooth [®] Class II |
| Range | up to 10 m |
| Power supply | 6 x 1.5 V cells type IEC LR6 (AA, MN1500, HP7, AM3 R6HP) Alkaline |
| | 6 x 1.2 NiMH rechargeable cells may be used. |
| Battery life | 3000 insulation tests with duty cycle of 5 sec ON /55 sec OFF @ 1000 V into 1 M Ω Charger (Optional): 12-15 V dc (accessory interface) |
| Dimensions | Instrument: 228 mm x 108 mm x 63 mm (9.00 in x 4.25 in x 2.32 in) |

| | |
|-------------------------------------|---|
| Weight | 815 g, (1.8 lb) |
| Weight (instrument and case) | 1.75 kg (3.86 lb) |
| Fuse | Use only 2 x 500 mA (FF) 1000 V 32 x 6 mm ceramic fuse of high breaking capacity HBC 30 kA minimum. Glass fuses MUST NOT be fitted |
| Safety protection | The instruments meet EN 61010-1 (1995) to 600 V phase to earth, Category IV. Refer to safety warnings supplied |
| EMC | In accordance with IEC 61326 including amendment No.1 |
| Temperature coefficient | <0,1% per $^{\circ}$ C up to 1 G Ω <0,1% per $^{\circ}$ C per G Ω above 1 G Ω |
| Environmental: | |
| Operating temperature range | -10 $^{\circ}$ C to +55 $^{\circ}$ C |
| Humidity | 90% RH at 40 $^{\circ}$ C max |
| Storage temperature range | -25 $^{\circ}$ C to +70 $^{\circ}$ C |
| Calibration temperature | +20 $^{\circ}$ C |
| Maximum altitude | 2000 m |
| IP rating | IP 54 |

The Bluetooth [®] word mark and logos are registered trademarks owned by Bluetooth SIG, Inc and is used under licence.

ORDERING INFORMATION

| Description | Order Code | Description | Order Code |
|--|------------|---|------------|
| Language group 1 - English - French - German - Dutch | | Included Accessories | |
| MIT2500 - 50 V to 2500 V Insulation tester + Store and Download | 1004-745 | Red/Black/Blue silicone test leads with prods and clips | |
| | | 2.5 kV Red/Black/Blue silicone test leads with clips | |
| | | Owners Information CD | |
| | | Batteries 6 x AA Alkaline | |
| | | Carry Case | |
| Language group 2 - English - Spanish - Italian - Portuguese | | Optional Accessories | |
| MIT2500 - 50 V to 2500 V Insulation tester + Store and Download | 1006-764 | Mains Charger kit | 1007-464 |
| | | 12 V DC car charger (requires mains charger kit) | 1004-183 |
| | | Switched probe SP5 | 1007-157 |
| | | Test lead set and crocodile clips | 1002-001 |
| | | 2 wire 500 mA fused test lead set | 1002-015 |
| | | Batteries (6 x NiMH) | 1002-735 |
| Language group 3 - English - Arabic - Turkish - French | | | |
| MIT2500 - 50 V to 2500 V Insulation tester + Store and Download | 1006-765 | | |
| Language group 4 - English - Czech - Slovak - Polish | | | |
| MIT2500 - 50 V to 2500 V Insulation tester + Store and Download | 1006-766 | | |
| Language group 5 - English - Chinese - Japanese - Korean | | | |
| MIT2500 - 50 V to 2500 V Insulation tester + Store and Download | 1006-767 | | |
| Language group 6 - English - Hungarian - Romanian - Russian | | | |
| MIT2500 - 50 V to 2500 V Insulation tester + Store and Download | 1006-768 | | |
| Language group 7 - English - Finnish - Norwegian - Swedish | | | |
| MIT2500 - 50 V to 2500 V Insulation tester + Store and Download | 1006-769 | | |