

Adapter Sleeves - standard configurations

Our adapter sleeves are designed for use with SIKA dry block calibrators. The sleeves are configured with various diameter bores to accommodate industry standard temperature sensors. We provide several standard configurations for quick delivery.

Adapter sleeves	Dimensions	Ø 60 mm (Aluminium)	Ø 28 mm (Brass alloy)	Ø 18 mm (Brass alloy)
Standard	Bores	TP 3M Series TP M Series	TP 37 Series TP 17 Series	TP 18 Series
		1x 3.5 mm (1/8 in) 1x 6.5 mm (1/4 in)	✓	✓
		1x 3.5 mm (1/8 in) 1x 6.5 mm (1/4 in) 1x 13.5 mm (1/2 in)	✓	✓
		1x 3.5 mm (1/8 in) 1x 5.0 mm (3/16 in) 1x 6.5 mm (1/4 in) 1x 9.5 mm (3/8 in)	✓	✓
		1x 3.5 mm (1/8 in) 6x 6.5 mm (1/4 in)	✓	✓
		1x 3.5 mm (1/8 in) 2x 5.0 mm (3/16 in) 2x 6.5 mm (1/4 in) 2x 9.5 mm (3/8 in)	✓	✓
		Blank sleeve	✓	✓
		1x 10.5 mm (3/8 in)		✓
		1x 13.5 mm (1/2 in)		✓



For other configurations - consult factory