



Premium ultrasonic thickness gauge

Features

- **External sensor** for difficult-to-access measurements
- **Base plate for adjustment** included
- **1 Data interface RS-232**
- **2** Delivered in a hard carrying case
- **Scan mode** (10 measurements per sec.) or single point measuring mode possible
- **Internal memory** for up to 20 files (with up to 100 values per file)
- **Limit value function**, programming of Max./Min., in pull and push direction, with output of audible and optical signal.
- Selectable measuring units: mm, inch
- Robust metal housing

Technical data

- Precision: 0,5 % of [Max] ± 0,04 mm
- Dimensions W×D×H 76×32×132 mm
- Battery operation, batteries standard 2× 1.5V AA
- Net weight approx. 345 g

Accessories

- **Software**, interface cable included, SAUTER ATU-04
- **External sensor**, 2,5 MHz, Ø 14 mm, for thick samples, in particular cast iron with rough upper surfaces: Measuring range 3–300 mm (steel), SAUTER ATU-US01
- **External sensor**, 7 MHz, Ø 6 mm, for thin test materials: Measuring range 0,75–80 mm (steel), SAUTER ATU-US02
- **External sensor**, 5 MHz, Ø 6 mm, SAUTER ATB-US01

- **External sensor**, 5 MHz, Ø 12 mm, for hot test materials: Measuring range (steel) 3–200 mm at temperatures of up to 300 °C, SAUTER ATB-US02
- **External sensor**, 5 MHz, Ø 10 mm, SAUTER ATU-US09
- **External sensor**, 5 MHz, Ø 10 mm, transducer at an angle of 90°, SAUTER ATU-US10
- **External sensor**, 6 MHz, Ø 6 mm, for thin test materials: Measuring range (steel) 1–50 mm, SAUTER ATB-US01
- **3 Thermal printer**, SAUTER ATU-05
- **Paper rolls**, 1 piece, for SAUTER ATU-05, SAUTER ATU-US11
- **Ultrasound contact gel**, standard, can be reordered, approx. 60 ml, SAUTER ATB-US03

































STANDARD



OPTION



Model	Measuring range [Max] mm	Readout [d] mm	Sensor	Sound velocity m/sec	Option Factory calibration certificates	
					KERN	
SAUTER TU 80-0.01US.	0,75–80	0,01	7 MHz Ø 6 mm	1000–9999	961-113	
TU 230-0.01US.	1,2–200 230	0,01 0,1	5 MHz Ø 10 mm	1000–9999	961-113	
TU 300-0.01US.	3–200 300	0,01 0,1	2,5 MHz Ø 14 mm	1000–9999	961-113	

	Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.		Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc.		Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.
	Calibration block: standard for adjusting or correcting the measuring device.		Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements.		Power supply: Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request.
	Peak hold function: capturing a peak value within a measuring process.		Statistics: using the saved values, the device calculates statistical data, such as average value, standard deviation etc.		Motorised drive: The mechanical movement is carried out by a electric motor.
	Scan mode: continuous capture and display of measurements.		PC Software: to transfer the measurements from the device to a PC.		Motorised drive: The mechanical movement is carried out by a synchronous motor (stepper).
	Push and Pull: the measuring device can capture tension and compression forces.		Printer: a printer can be connected to the device to print out the measurements.		Fast-Move: the total length of travel can be covered by a single lever movement.
	Length measurement: captures the geometric dimensions of a test object or the movement during a test process.		GLP/ISO record keeping: of measurements with date, time and serial number. Only with SAUTER printers.		DAkkS calibration possible: The time required for DAkkS calibration is shown in days in the pictogram.
	Focus function: increases the measuring accuracy of a device within a defined measuring range.		Measuring units: Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details.		Factory calibration: The time required for factory calibration is specified in the pictogram.
	Internal memory: to save measurements in the device memory.		Measuring with tolerance range: Upper and lower limiting can be programmed individually, e.g. for sorting and dosing.		Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.
	Data interface RS-232: bidirectional, for connection of printer and PC.		ZERO: Resets the display to "0".		Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.
	Data interface USB: To connect the balance to a printer, PC or other peripheral devices.		Battery operation: Ready for battery operation. The battery type is specified for each device.		Warranty: The warranty period is shown in the pictogram.
	Data interface Infrared: To transfer data from the balance to a printer, PC or other peripheral devices.		Rechargeable battery pack: rechargeable set.		

Your SAUTER specialist dealer: