KERN CCS30K0.1.







Measuring system	
Adjustment options:	External calibration
Linearity:	200 mg
Recommended adjusting weight:	30000 g (M1)
Repeatability:	100 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	kg lb

Display digit height:	2 cm		
Counting			
Counting resolution:	300000		
Mininum piece weight at piece counting (Laboratory:	100 mg		
Mininum piece weight at piece counting (Normal):	1 g		

Display

Reference weight:

Functions	
Conversion function:	yes
Counting function:	yes
Function to save totals:	yes
PRE-TARE function:	yes
Weighing with tolerance range:	yes

yes

Environmental conditions					
Maximum humidity:	80 %				
Maximum operating temperature:	40 °C				
Minimum ambient temperature:	0°C				
Minimum humidity:	0 %				

	\triangle	W	Or	CI	In	n	W
ш	U	w	CI.	Sι	IJν	ν	IУ

Charging time: 12 h

Input voltage: 220 V - 240 V AC 50 Hz
Mains adapter/adapter included: CH EURO UK US

Operating time (Backlight on): 70 h

Rechargeable battery: Rchrg. battery optional

Service

Adjustment at the location of installation: abhängig von

Auflösung/Max | depends on resolution and capacity

320 x 350 x 120 mm

MULTI

DAkkS Certificate: 962-128-128

Category

Brand: KERN

Product Group: Counting system

Packaging & shipping

Delivery: 24 h

Dimensions packaging (WxDxH): 940 x 640 x 225 mm

Gross weight: 15,900 kg
Net weight: 9,700 kg
Shipping method: Parcel service

Construction

Cable length: 1,500 m
Cable length of display device: 2,500 m
Casing material: Plastic

Dimensions of weighing plate 400 x 300 x 120 mm

(WxDxH):

Level indicator: yes

Material weighing plate: stainless steel


Overall dimensions mounted (WxDxH):

Revolving screw feet: yes

Weighing surface (WxD): 400 x 300 mm

Piktogramme

STANDARD



OPTION

