
KERN CCS30K0.01.







Measuring system	
Adjustment options:	External calibration
Linearity:	30 mg
Recommended adjusting weight:	30000 g (M1)
Repeatability:	20 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	kg lb

Display digit height:	2 cm
Counting	
Counting resolution:	600000
Mininum piece weight at piece counting (Laboratory:	50 mg
Mininum piece weight at piece counting (Normal):	500 mg

yes

Display

Reference weight:

Functions	
Conversion function:	yes
Counting function:	yes
Function to save totals:	yes
PRE-TARE function:	yes
Weighing with tolerance range:	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C
Minimum humidity:	0 %

	α	NIC	١r	OI.	ın	n	V
P	UΝ	WE	7L	\mathbf{o}	עג	24	M

Charging time: 12 h

Input voltage: 220 V - 240 V AC 50 Hz
Mains adapter/adapter included: CH EURO UK US

Mains adapter/adapter included: CH EU Operating time (Backlight on): 70 h

Rechargeable battery: Rchrg. battery optional

Service

Adjustment at the location of installation: abhängig von

Auflösung/Max | depends on resolution and capacity

DAkkS Certificate: 962-128-127

Category

Brand: KERN

Product Group: Counting system

Packaging & shipping

Delivery: 48 h

Dimensions packaging (WxDxH): 940 x 640 x 230 mm

Gross weight: 15,900 kg
Net weight: 12,050 kg
Shipping method: Parcel service

Construction

Cable length: 1,500 m
Cable length of display device: 2,500 m
Casing material: Plastic

Dimensions of weighing plate 400 x 300 x 128 mm

(WxDxH):

Level indicator: yes

Material weighing plate: stainless steel

Overall dimensions mounted 320 x 330 x 125 mm


(WxDxH):

Revolving screw feet: yes

Weighing surface (WxD): 400 x 300 mm

Piktogramme

STANDARD



OPTION

