KERN EOC6K-4A



All-round parcel scale with practical Flip/Flop display device for greatest ease of use



Measuring system				
Adjustment options:	External calibration			
Linearisation (points):	3			
Linearity:	1,500 g			
Readability [d]:	500 mg			
Recommended adjusting weight:	6 kg (M1)			
Repeatability:	500 mg			
Resolution:	12000			
Stabilisation time under laboratory conditions:	2 s			
Tare range:	-6000000 mg			
Warm up time:	30 min			
Weighing capacity [Max]:	6 kg			
Weighing system:	Strain gauge			
Weighing units:	g kg lb oz			
Display				
Display digit height:	2,400 cm			
Counting				
Counting resolution:	24000			
Mininum piece weight at piece counting (Laboratory:	250 mg			

Functions

counting (Normal):

Mininum piece weight at piece

Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

2,500 g

Environmental conditions			
Maximum humidity:	80 %		
Maximum operating temperature:	40 °C		
Minimum ambient temperature:	-10 °C		
Minimum humidity:	0 %		
Power supply			
Charging time:	3 h		
Input voltage:	100V-240V 0.4A		
Mains adapter/adapter included:	CH EURO UK US		
n/a:	Mains adapter external		
Power supply			
Operating time (Backlight off):	43 h		
Operating time (Backlight on):	26 h		
Rechargeable battery:	Rchrg. battery optional -		
	intern		
Service			
Adjustment at the location of installatio	n:961-248		
DAkkS Certificate:	963-128		
Category			
Brand:	KERN		
Category:	Balances		
Product Group:	Industiral scale		
,	industrial scale		
Packaging & shipping			
	24 h		
Packaging & shipping			
Packaging & shipping Delivery:	24 h		
Packaging & shipping Delivery: Dimensions packaging (WxDxH):	24 h 560 x 400 x 160 mm		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	24 h 560 x 400 x 160 mm 7,500 kg		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service		
Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m		
Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:ConstructionCable length of display device:Dimensions of display device(WxDxH):Dimensions of weighing plate	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm		
Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:ConstructionCable length of display device:Dimensions of display device(WxDxH):Dimensions of weighing plate(WxDxH):	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm		
Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:ConstructionCable length of display device:Dimensions of display device(WxDxH):Dimensions of weighing plate(WxDxH):of stand:	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm		
Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:ConstructionCable length of display device:Dimensions of display device(WxDxH):Dimensions of weighing plate(WxDxH):of stand:Level indicator:	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes		
Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:ConstructionCable length of display device:Dimensions of display device(WxDxH):Dimensions of weighing plate(WxDxH):of stand:Level indicator:Material weighing plate:Revolving screw feet:Wall mount:	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 333 cm yes stainless steel		
Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:ConstructionCable length of display device:Dimensions of display device(WxDxH):Dimensions of weighing plate(WxDxH):of stand:Level indicator:Material weighing plate:Revolving screw feet:	24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel yes		

KERN EOC6K-4A



All-round parcel scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

CAL EXT	• AMA • RS 232	KCP Protocol	GLP PRINTER	PCS	SUM	% Percent	-√+ ⊙ ଚୁ୬ TOL	MOVE
000 IP 65		DMS	1 DAY					

OPTION

)	DAkkS
ACCU	+3 DAYS