KERN EWJ300-3H



High-quality precision balance with automatic internal adjustment, also with EC type approval



| Maximum humid Maximum operat |
|---------------------------------|
| Minimum ambier |
| Power supply |
| Charging time: |
| Input voltage: |
| Mains adapter/a |
| |
| n/a: |
| Power supply |
| Operating time (I |
| Operating time (I |
| Rechargeable ba |
| |
| Service |
| DAkkS Certificat |
| Category |
| Brand: |
| Category: |
| Product Group: |
| Packaging & s |
| Delivery: |
| Dimensions pack |
| Gross weight: |
| Net weight: |
| Shipping method |
| Construction |
| Casing material: |
| Dimensions draf |

| Measuring system | |
|--|--|
| Adjustment options: | Internal calibration (auto) |
| Linearity: | 5 mg |
| Minimum weight (USP): | 4 g |
| Readability [d]: | 1 mg |
| Repeatability: | 2 mg |
| Resolution: | 300000 |
| Stabilisation time under laboratory conditions: | 3 s |
| Warm up time: | 2 h |
| Weighing capacity [Max]: | 300 g |
| Weighing system: | Strain gauge |
| Weighing units: | ct dwt lb mo oz ozt tl (HK) tl (Singap. Malays) tl (Tw) |
| Display | |
| Display digit height: | 1,650 cm |
| Counting | |
| · · · · · · | |
| Counting resolution: | 150000 |
| | 150000 2 mg |
| Counting resolution: Mininum piece weight at piece | |
| Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece | 2 mg |
| Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece counting (Normal): | 2 mg |
| Counting resolution: Mininum piece weight at piece counting (Laboratory: Mininum piece weight at piece counting (Normal): Functions | 2 mg 20 mg |

| Environmental conditions | |
|---|----------------------------------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 15 °C |
| Power supply | |
| Charging time: | 4 h |
| Input voltage: | 100 V - 240 V 50 / 60 Hz |
| Mains adapter/adapter included: | CH EURO UK US |
| | |
| n/a: | Mains adapter external |
| Power supply | |
| Operating time (Backlight off): | 15 h |
| Operating time (Backlight on): | 10 h |
| Rechargeable battery: | Rchrg. battery optional - intern |
| Service | |
| DAkkS Certificate: | 963-127 |
| Category | |
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Precision balance |
| Packaging & shipping | |
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 400 x 275 x 410 mm |
| Gross weight: | 5,110 kg |
| Net weight: | 3,572 kg |
| Shipping method: | Parcel service |
| Construction | |
| Casing material: | Plastic |
| Dimensions draft shield (WxDxH): | 180 x 191 x 230 mm |
| Dimensions housing (WxDxH): | 220 x 340 x 321 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 220 x 340 x 321 mm |
| Revolving screw feet: | yes |
| Maighing on a se (MarDell) | |
| vveigning space (vvxDxH): | 155 x 175 x 217 mm |
| Weighing space (WxDxH): Weighing surface (d): | 155 x 175 x 217 mm 80 |

KERN EWJ300-3H



High-quality precision balance with automatic internal adjustment, also with EC type approval [M]

##