KERN EOC60K-3



All-round parcel scale with practical Flip/Flop display device for greatest ease of use



| Adjustment options: | External calibration | | |
|---|----------------------|--|--|
| Linearisation (points): | 3 | | |
| Linearity: | 3g 6g | | |
| Readability [d]: | 1 g 2 g | | |
| Recommended adjusting weight: | 60 kg (F2) | | |
| Repeatability: | 1 g 2 g | | |
| Resolution: | 30 30.000 | | |
| Stabilisation time under laboratory conditions: | 2 s | | |
| Tare range: | -60000000 mg | | |
| Warm up time: | 2 h 2 h | | |
| Weighing capacity [Max]: | 30 kg 60 kg | | |
| Weighing system: | Strain gauge | | |
| Weighing units: | g kg lb oz | | |
| Display | | | |
| Display digit height: | 2,400 cm | | |
| Counting | | | |
| Counting resolution: | 30000 | | |
| Mininum piece weight at piece counting (Laboratory: | 2 g | | |
| Mininum piece weight at piece counting (Normal): | 20 g | | |

Functions

| Counting function: | yes | |
|--|-----|--|
| Percentage determination: | yes | |
| Vibration-free weighing (Animal weighing program): | yes | |
| Weighing with tolerance range: | yes | |

| Environmental conditions | | | | |
|--|---|--|--|--|
| Maximum humidity: | 80 % | | | |
| Maximum operating temperature: | 40 °C | | | |
| Minimum ambient temperature: | -10 °C | | | |
| Minimum humidity: | 0 % | | | |
| Power supply | | | | |
| Charging time: | 3 h | | | |
| Input voltage: | 100V-240V 0.4A | | | |
| Mains adapter/adapter included: | CH EURO UK US | | | |
| | | | | |
| n/a: | Mains adapter external | | | |
| Power supply | | | | |
| Operating time (Backlight off): | 43 h | | | |
| Operating time (Backlight on): | 26 h | | | |
| Rechargeable battery: | Rchrg. battery optional - | | | |
| | intern | | | |
| Service | | | | |
| Adjustment at the location of installation | on:961-249 | | | |
| DAkkS Certificate: | 963-129 | | | |
| | | | | |
| Category | | | | |
| Category Brand: | KERN | | | |
| | KERN Balances | | | |
| Brand: | | | | |
| Brand: Category: | Balances | | | |
| Brand: Category: Product Group: | Balances | | | |
| Brand: Category: Product Group: Packaging & shipping | Balances Industiral scale | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: | Balances Industiral scale 24 h | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): | Balances Industiral scale 24 h 560 x 400 x 160 mm | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes | | | |
| Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of weighing plate (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate: | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel | | | |
| Brand: Category: Product Group: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate: Revolving screw feet: | Balances Industiral scale 24 h 560 x 400 x 160 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel yes | | | |

KERN EOC60K-3



All-round parcel scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

| CAL EXT | • AMA • RS 232 | KCP Protocol | GLP PRINTER | PCS | SUM | % Percent | -√+ ⊙ ଚୁ୬ TOL | MOVE |
|--------------|-------------------|-----------------|----------------|-----|-----|--------------|---------------------|------|
| 000 IP 65 | | DMS | 1 DAY | | | | | |

OPTION

|) | DAkkS |
|-----------|---------|
| ACCU | +3 DAYS |