KERN EOC10K-4







Measuring system	
Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	600 mg 1500 mg
Readability [d]:	200 mg 500 mg
Recommended adjusting weight:	15 kg (F2)
Repeatability:	200 mg 500 mg
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-15000000 mg
Warm up time:	2 h 2 h
Weighing capacity [Max]:	6 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	g kg lb oz

Tare range:	-15000000 mg
Warm up time:	2 h 2 h
Weighing capacity [Max]:	6 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	g kg lb oz
Display	
Display	

Display digit height:

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	500 mg
Mininum piece weight at piece counting (Normal):	5 g

2,400 cm

Functions		
Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

r ower supply	
Charging time:	3 h
Input voltage:	100V-240V 0.4A
Mains adapter/adapter included:	CH EURO UK US

n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional -

intern

Service		
Adjustment at the location of ins	stallation: 961-248	
DAkkS Certificate:	963-128	
Category		

Salege. j	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	300 x 300 x 110 mm
of stand:	33 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 300 mm

KERN EOC10K-4



All-round parcel scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD



OPTION

