KERN EOC10K-3







Measuring system	
Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	6 g 15 g
Readability [d]:	2 g 5 g
Recommended adjusting weight:	12 kg (M1)
Repeatability:	2 g 5 g
Resolution:	3 2.400
Stabilisation time under laboratory conditions:	2 s
Tare range:	-15000000 mg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	6 kg 12 kg
Weighing system:	Strain gauge
Weighing units:	g kg lb oz

Display	
Display digit height:	2.400 cm

24000
500 mg
5 g

Functions		
Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	3 h
Input voltage:	100V-240V 0.4A
Mains adapter/adapter included:	CH EURO UK US

n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h

•	•	•	•	•	
Recharg	eable	batter	y:		Rchrg. battery optional -
					intern

Service		
Adjustment at the location of installa	tion: 961-248	
DAkkS Certificate:	963-128	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping

r ackaging a shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	560 x 400 x 160 mm
Gross weight:	7,500 kg
Net weight:	6,500 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	300 x 300 x 110 mm
of stand:	33 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 300 mm

KERN EOC10K-3



All-round parcel scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD



OPTION

