

KERN HFD10T-3

Robust, high-resolution crane scale up to 12 t



Functions

Standby function: yes

Environmental conditions

Maximum humidity: 95 %
Maximum operating temperature: 40 °C
Minimum ambient temperature: -10 °C
Minimum humidity: 10 %

Power supply

Battery: 1x12V Type 23A
Charging time: 12 h
Input voltage: 110 V - 240 V AC
Mains adapter/adaptor included: CH EURO UK

n/a: Mains adapter external

Power supply

Operating time (Backlight off): 70 h
Operating time (Backlight on): 30 h

Service

Adjustment at the location of installation: 961-252

DAkkS Certificate: 963-133H

Category

Brand: KERN
Category: Balances
Product Group: Crane scale

Packaging & shipping

Delivery: 24 h
Dimensions packaging (WxDxH): 730 x 280 x 265 mm
Gross weight: 21,200 kg
Net weight: 20 kg
Shipping method: Parcel service
UN number: 3481

Construction

Casing material: Cast aluminium alloys
Dimensions (WxDxH): 194 x 471 x 129 mm
Dimensions of display device (WxDxH): 160 x 120 x 160 mm

Measuring system

Adjustment options: External calibration
Linearity: 2 kg | 4 kg | 10 kg
Precision (of [Max]): 0,200 %
Readability [d]: 1 kg | 2 kg | 5 kg
Repeatability: 1 kg | 2 kg | 5 kg
Resolution: 3 3.000 2.400
Stabilisation time under laboratory conditions: 2 s
Tare range: 11,995 t
Warm up time: 10 min | 10 min | 10 min
Weighing capacity [Max]: 3 t | 6 t | 12 t
Weighing system: Strain gauge
Weighing units: kg

Display

Display digit height: 3 cm

KERN HFD10T-3

Robust, high-resolution crane scale up to 12 t



Piktogramme

STANDARD

