
# KERN IFB 600K-1M







Measuring system	
Adjustment options:	External calibration
Linearity:	100 g   200 g
Readability [d]:	100 g   200 g
Recommended adjusting weight:	600 kg (M1)
Repeatability:	100 g   200 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-600 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	300 kg   600 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Display digit height:	5,200 cm

Technical data about verification	
Minimum load [Min]:	2 kg   4 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	100 g   200 g

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	20 g
Mininum piece weight at piece counting (Normal):	200 g

Functions	
Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40°C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter/adapter included:	CH EURO UK US
n/a:	
II/a.	Mains adapter external
Power supply	Mains adapter external
	Mains adapter external  35 h
Power supply	
Power supply Operating time (Backlight off):	35 h
Power supply Operating time (Backlight off): Operating time (Backlight on):	35 h 8 h Rchrg. battery optional
Power supply Operating time (Backlight off): Operating time (Backlight on): Rechargeable battery:	35 h 8 h Rchrg. battery optional (factory)
Power supply Operating time (Backlight off): Operating time (Backlight on): Rechargeable battery: Service	35 h 8 h Rchrg. battery optional (factory)
Power supply Operating time (Backlight off): Operating time (Backlight on): Rechargeable battery:  Service Adjustment at the location of installation	35 h 8 h Rchrg. battery optional (factory)
Power supply Operating time (Backlight off): Operating time (Backlight on): Rechargeable battery:  Service Adjustment at the location of installation DAkkS Certificate:	35 h 8 h Rchrg. battery optional (factory) :961-250
Power supply Operating time (Backlight off): Operating time (Backlight on): Rechargeable battery:  Service Adjustment at the location of installation DAkkS Certificate: Verification:	35 h 8 h Rchrg. battery optional (factory) :961-250
Power supply Operating time (Backlight off): Operating time (Backlight on): Rechargeable battery:  Service Adjustment at the location of installation DAkkS Certificate: Verification:  Category	35 h 8 h Rchrg. battery optional (factory) :961-250 963-130 965-230
Power supply Operating time (Backlight off): Operating time (Backlight on): Rechargeable battery:  Service Adjustment at the location of installation DAkkS Certificate: Verification:  Category Brand:	35 h 8 h Rchrg. battery optional (factory) :961-250 963-130 965-230 KERN

48 h

70 kg

65 kg

1250 x 800 x 380 mm

Freight forwarder

Delivery:

Gross weight:

Shipping method:

Net weight:

Dimensions packaging (WxDxH):

## KERN IFB 600K-1M



Platform scale in heavy version with EC type approval [M], now also up to [Max] 600 kg

Construction	
Cable length of display device:	3 m
Casing material:	Plastic
Dimensions of display device (WxDxH):	250 x 160 x 58 mm
Dimensions of weighing plate (WxDxH):	800 x 600 x 200 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	800 x 600 x 190 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	800 x 600 mm

## Piktogramme

#### STANDARD



#### **OPTION**



### **FACTORY**

