KERN IOC100K-2LM



All-round platform scale with a range of communication options and EC type approval [M]



Measuring system			
Adjustment options:	External calibration		
Linearisation (points):	3 60 g 150 g		
Linearity:			
Readability [d]:	20 g 50 g		
Recommended adjusting weight:	150 kg (M1)		
Repeatability:	20 g 50 g		
Resolution:	3 3.000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-150 kg		
Warm up time:	10 min 10 min		
Weighing capacity [Max]:	60 kg 150 kg		
Weighing system:	Strain gauge		
Weighing units:	kg		

Display

Display digit height:

2,400 cm

Technical data about verification	
Minimum load [Min]:	400 g 1000 g
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	20 g 50 g

Counting

Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	5 g
Mininum piece weight at piece counting (Normal):	50 g

FunctionsCounting function:yesPercentage determination:yesPRE-TARE function:yesVibration-free weighing (Animal weighing program):yesWeighing with tolerance range:yesEnvironmental conditionsyesMaximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0 %Charging time:3 hInput voltage:100V-240V AC 50/60Hz 0,400 AmaxMains adapter/adapter included:EURO UK USPower supplyYesNains adapter externalYes
Percentage determination:yesPRE-TARE function:yesVibration-free weighing (Animal weighing program):yesWeighing with tolerance range:yesEnvironmental conditions80 %Maximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0 %Charging time:3 hInput voltage:100V-240V AC 50/60Hz 0,400 AmaxMains adapter/adapter included:EURO UK USn/a:Mains adapter external
PRE-TARE function:yesVibration-free weighing (Animal weighing program):yesWeighing with tolerance range:yesEnvironmental conditions80 %Maximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0Charging time:3 hInput voltage:100V-240V AC 50/60Hz 0,400 AmaxMains adapter/adapter included:EURO UK USn/a:Mains adapter external
Vibration-free weighing (Animal weighing program):yesWeighing with tolerance range:yesEnvironmental conditions80 %Maximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0 %Charging time:3 hInput voltage:100V-240V AC 50/60Hz 0,400 AmaxMains adapter/adapter included:EURO UK USn/a:Mains adapter external
weighing program): Weighing with tolerance range: Environmental conditions Maximum humidity: Maximum operating temperature: 40 °C Minimum ambient temperature: -10 °C Minimum humidity: 0 % Power supply Charging time: 100V-240V AC 50/60Hz 0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
Weighing with tolerance range:yesEnvironmental conditionsMaximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0 %Charging time:3 hInput voltage:100V-240V AC 50/60Hz 0,400 AmaxMains adapter/adapter included:EURO UK USn/a:Mains adapter external
Maximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supplyCharging time:3 hInput voltage:100V-240V AC 50/60Hz0,400 Amax0,400 AmaxMains adapter/adapter included:EURO UK USn/a:Mains adapter external
Maximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supplyCharging time:3 hInput voltage:100V-240V AC 50/60Hz0,400 Amax0,400 AmaxMains adapter/adapter included:EURO UK USn/a:Mains adapter external
Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0 %Charging time:3 hInput voltage:100V-240V AC 50/60Hz 0,400 AmaxMains adapter/adapter included:EURO UK USn/a:Mains adapter external
Minimum ambient temperature: -10 °C Minimum humidity: 0 % Power supply 0 % Charging time: 3 h Input voltage: 100V-240V AC 50/60Hz 0,400 Amax 0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
Minimum humidity: 0 % Power supply 0 % Charging time: 3 h Input voltage: 100V-240V AC 50/60Hz 0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
Power supply Charging time: 3 h Input voltage: 100V-240V AC 50/60Hz 0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
Charging time: 3 h Input voltage: 100V-240V AC 50/60Hz 0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
Input voltage: 100V-240V AC 50/60Hz 0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
Input voltage: 100V-240V AC 50/60Hz 0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
0,400 Amax Mains adapter/adapter included: EURO UK US n/a: Mains adapter external
n/a: Mains adapter external
Powersupply
Operating time: 100 h
Operating time (Backlight off): 43 h
Operating time (Backlight on): 26 h
Rechargeable battery: Rchrg. battery optional -
intern
Service
Adjustment at the location of installation: 961-249
Aujustinent at the location of installation. 901-249
DAkkS Certificate: 963-129
Category
Brand: KERN
Category: Balances
Product Group: Industiral scale
Packaging & shipping
Delivery: 24 h
Dimensions packaging (WxDxH): 1090 x 660 x 170 mm
Gross weight: 24,720 kg
Net weight: 21,900 kg
Shipping method: Parcel service

KERN IOC100K-2LM



All-round platform scale with a range of communication options and EC type approval [M]

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	260 x 115 x 70 mm
Dimensions of weighing plate (WxDxH):	650 x 500 x 150 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	650 x 500 mm

Piktogramme

STANDARD

	• 888. •	KCP	GLP			%	+ ③ ③)	^-
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	SUM	PERCENT	TOL	MOVE
666	B							
IP 65	MULTI	DMS	1 DAY					

OPTION

E B	DAkkS
ACCU	+3 DAYS

FACTORY

	•	*	((1-	-0_0-	문	Μ	
ALIBI	USB	BT 4.0	WLAN	SWITCH	LAN	+3 DAYS	