

# KERN IOC60K-2LM

All-round platform scale with a range of communication options and EC type approval [M]



## Measuring system

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	30 g   60 g
Readability [d]:	10 g   20 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	10 g   20 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	30 kg   60 kg
Weighing system:	Strain gauge
Weighing units:	kg

## Display

Display digit height:	2,400 cm
-----------------------	----------

## Technical data about verification

Minimum load [Min]:	200 g   400 g
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	10 g   20 g

## Counting

Counting resolution:	30000
Minimum piece weight at piece counting (Laboratory):	2 g
Minimum piece weight at piece counting (Normal):	20 g

## Functions

Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

## Power supply

Charging time:	3 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter/adaptor included:	EURO UK US

n/a:	Mains adapter external
------	------------------------

## Power supply

Operating time:	100 h
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional - intern

## Service

Adjustment at the location of installation: 961-249

DAkkS Certificate:	963-129
--------------------	---------

## Category

Brand:	KERN
Category:	Balances
Product Group:	Industrial scale

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	885 x 490 x 175 mm
Gross weight:	13,700 kg
Net weight:	11,230 kg
Shipping method:	Parcel service

# KERN IOC60K-2LM



All-round platform scale with a range of communication options and EC type approval [M]

## Construction

Cable length of display device:	3 m
Dimensions of display device (WxDxH):	260 x 115 x 70 mm
Dimensions of weighing plate (WxDxH):	500 x 400 x 120 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	500 x 400 mm

## Piktogramme

### STANDARD



### OPTION



### FACTORY

