KERN IXS30K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system

5 ,	
Adjustment options:	External calibration
Linearity:	3 g
Number of weighing ranges:	1
Readability [d]:	1 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	1 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height:

Counting		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	1 g	
Mininum piece weight at piece counting (Normal):	10 g	

5,500 cm

Functions

Counting function:	yes
Data hold function:	yes
Help function on the display:	yes
Peak function:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	12 h			
Input voltage:	220 V - 240 V AC 50 Hz			
Mains adapter/adapter included:	EURO			
Operating time (Backlight off):	80 h			
Operating time (Backlight on):	40 h			
Rechargeable battery:	Rchrg. battery optional (factory)			
Service				
Adjustment at the location of installation	n:961-248			
DAkkS Certificate:	963-128			
Category				
Brand:	KERN			
Category:	Balances			
Category: Product Group:	Balances Industiral scale			
• •				
Product Group:				
Product Group: Packaging & shipping	Industiral scale			
Product Group: Packaging & shipping Delivery:	Industiral scale			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Industiral scale 24 h 500 x 775 x 240 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Industiral scale 24 h 500 x 775 x 240 mm 23 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg Parcel service			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg Parcel service 2,500 m			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg Parcel service 2,500 m 232 x 170 x 80 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg Parcel service 2,500 m 232 x 170 x 80 mm 500 x 400 x 123 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator:	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg Parcel service 2,500 m 232 x 170 x 80 mm 500 x 400 x 123 mm yes			
Product Group:Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:ConstructionCable length of display device:Dimensions of display device(WxDxH):Dimensions of weighing plate(WxDxH):Level indicator:Material weighing plate:	Industiral scale 24 h 500 x 775 x 240 mm 23 kg 20,500 kg Parcel service 2,500 m 232 x 170 x 80 mm 500 x 400 x 123 mm yes stainless steel			

KERN IXS30K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Piktogramme

STANDARD

CAL EXT PCS	SUM	-√+ ত ৢ৽ TOL	Move	6 6 5	000 IP 68	230 V
DMS 1 DAY						
OPTION						

DAkks +3 days

FACTORY

	-	*		Μ	
RS 232	RS 485	BT	ACCU	+3 DAYS	