## KERN IXS 60K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	6 g
Number of weighing ranges:	1
Readability [d]:	2 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	2 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60 kg
Warm up time:	2 h
Weighing capacity [Max]:	60 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Display digit height:	5,500 cm

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	2 g
Mininum piece weight at piece counting (Normal):	20 g

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service		
Adjustment at the location of ins	stallation: 961-249	
DAkkS Certificate:	963-129	
Category		
Brand:	KERN	

Balances

Industiral scale

Category:

Product Group:

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	490 x 770 x 255 mm
Gross weight:	23,800 kg
Net weight:	20,500 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	2,500 m
Dimensions of display device (WxDxH):	232 x 170 x 80 mm
Dimensions of weighing plate (WxDxH):	500 x 400 x 123 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	500 x 400 mm

## KERN IXS60K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

## Piktogramme STANDARD LA STAND