KERN IXS10K-4



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	1,500 g
Number of weighing ranges:	1
Readability [d]:	500 mg
Recommended adjusting weight:	15 kg (M1)
Repeatability:	500 mg
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-15 kg
Warm up time:	2 h
Weighing capacity [Max]:	15 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Display digit height:	5.500 cm

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	500 mg
Mininum piece weight at piece counting (Normal):	5 g

Functions		
Counting function:	yes	
Data hold function:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0 %	

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service		

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	490 x 570 x 212 mm
Gross weight:	7 kg
Net weight:	5,100 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	2,500 m
Dimensions of display device (WxDxH):	232 x 170 x 80 mm
Dimensions of weighing plate (WxDxH):	300 x 240 x 86 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 240 mm

KERN IXS10K-4



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Piktogramme STANDARD LA STAND