KERN KDP300-3

Universal weighing platforms for flexible connection in process chains





Measuring system	
Adjustment options:	External calibration
Linearity:	5 mg
Readability [d]:	1 mg
Repeatability:	2 mg
Resolution:	350000
Resolution (non verifiable):	350000
Warm up time:	2 h
Weighing capacity [Max]:	350 g
Weighing system:	Strain gauge

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	35 °C	
Minimum ambient temperature:	5°C	

Power supply	
Mains adapter/adapter included:	CH EURO UK US

Service	
DAkkS Certificate:	963-127

Category	
Brand:	KERN
Product Group:	Platform

Packaging & shipping	
Delivery:	24 h
Net weight:	1,040 kg
Shipping method:	Parcel service

Construction	
Cable length:	1,200 m
Dimensions draft shield (WxDxH):	157 x 157 x 80 mm
Dimensions housing (WxDxH):	165 x 166 x 75 mm
Level indicator:	yes
Overall dimensions mounted (WxDxH):	165 x 166 x 140 mm
Revolving screw feet:	yes
Weighing space (WxDxH):	146 x 146 x 80 mm
Weighing surface (d):	105

Piktogramme

STANDARD











OPTION



FACTORY



