

# KERN PFB 2000-2

Quick-displaying precision balance, now with larger housing for more secure footing



## Measuring system

Adjustment options:	External calibration
Linearity:	50 mg
Minimum weight (USP):	40 g
Readability [d]:	10 mg
Recommended adjusting weight:	2 kg (F1)
Repeatability:	20 mg
Resolution:	200000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	2 kg
Weighing system:	Strain gauge
Weighing units:	bat ct dot dwt g lb mo N oz ozt t tl (Cn) tl (HK) tl (Tw)

## Display

Display digit height:	1,500 cm
-----------------------	----------

## Counting

Counting resolution:	100000
Minimum piece weight at piece counting (Laboratory):	20 mg
Minimum piece weight at piece counting (Normal):	200 mg

## Functions

Counting function:	yes
Percentage determination:	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	30 °C
Minimum ambient temperature:	15 °C

## Power supply

Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter/adaptor included:	CH EURO UK US

n/a:	Mains adapter external
------	------------------------

## Service

DAkkS Certificate:	963-127
--------------------	---------

## Category

Brand:	KERN
Category:	Balances
Product Group:	Precision balance

## Packaging & shipping


Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 285 x 280 mm
Net weight:	2 kg
Shipping method:	Parcel service

## Construction

Casing material:	Plastic
Dimensions draft shield (WxDxH):	124 x 119 x 80 mm
Dimensions housing (WxDxH):	210 x 315 x 90 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing surface (d):	120

## Piktogramme

### STANDARD



### OPTION



### FACTORY



# KERN PFB 2000-2

Quick-displaying precision balance, now with larger housing for more secure footing

