

## First-class professional Class I, Class II sound level meter

### Features

- Ideal for measurements for workplaces outdoor, e.g. at airports, on building sites, in road construction etc. with broad access to spectrum thanks to the highly-accurate 24-Bit A/D converter
- **Floating point evaluation** for higher level of accuracy and better stability
- The **optimised analogue frontend switch** reduces the ambient noise and increases the linear measuring range
- A specially-developed algorithm permits a compliant **dynamic range of more than 120 dB!** (SW 1000: > 123 dB; SW 2000: > 122 dB)
- Three profiles and 14 user-defined measurements can be calculated in parallel with different frequency and time weighting
- **11 Different sound pressure levels can be selected**, such as, Laeq, LcPeak, LaF, LaFMax, LaFMin, SD, SEL, E
- **LN statistics and display of the graph showing the progression of time**
- **User-defined integral interval measurement** up to a maximum of 24 hours is possible
- **Frequency weighting** (filter) A, B, C, Z
- **Time interval** during measurement: F (fast), S (slow), I (pulse)
- Freely-definable limits for the output of an optical alarm signal
- **Peak hold function** to capture the peak value
- **2 Octavo function** for targeted sound analysis
- **TRACK function** with graphic display of a measurement
- Calibration mode (with optional calibrator)
- **3 Data logging function** with date and time in the device and data transfer using MicroSD (4G) memory card (included with delivery), RS-232 or USB
- **Trigger mode:** Analogue signal to switch the device on or off with 3.5 mm plug
- **Automatic measurement for timer function** is possible
- **Selectable frequency for recording measurements:** 10, 5, 2 Hz
- **Operating languages:** GB, DE, FR, ES, PT
- **4 Delivery** in robust transport case
- **5 Option** of fitting a stand on the rear of the housing, 1/4" thread

### Technical data

- Applicable standards: IEC61672-1:2014-07 GB/T3785.1-2010 1/1 Octavo in accordance with IEC 61260:2014
- 1/2 inch microphone
- Permissible ambient temperature range -10 °C/50 °C
- Output (direct or alternating current)
- AC (max 5 VRMS), DC (10 mV/DB)
- Mains operation as standard
- Battery operation, 4x 1.5V AA, not included, operating time up to 10 h
- Dimensions WxDxH 80x36x300 mm
- Net weight approx. 400 g

### Accessories

- **Plug-In for data transfer of measuring data** from the measuring instrument and transfer to a PC, e.g. in Microsoft Excel®, SAUTER AFI-1.0
- **5 Stand**, WxDxH 430x90x90 mm, 1250x750x750 mm (moved out), SAUTER SW-A05
- **6 SD-memory card**, storage capacity 4 GB, SAUTER SW-A04
- Calibrator for regular adjustment of the sound level meter, SAUTER ASU-01
- Foam draft shield, SAUTER SW-A03
































#### STANDARD



#### OPTION



Model	Accuracy class	Measuring range Linear dB	Frequency range dB	Sensitivity V/Pa	Option	
					DAKKS calibration certificate	Factory calibration certificates
SAUTER					DAKKS KERN	KERN
SW 1000	1	22-136	0,003-20 kHz	50 m V/Pa	963-281	961-281
SW 2000	2	25-136	0,02-12,5 kHz	40 m V/Pa	963-281	961-281

	<p><b>Adjusting program (CAL):</b> For quick setting of the balance's accuracy. External adjusting weight required.</p>		<p><b>Control outputs (optocoupler, digital I/O):</b> to connect relays, signal lamps, valves, etc.</p>		<p><b>Rechargeable battery pack:</b> rechargeable set.</p>
	<p><b>Calibration block:</b> standard for adjusting or correcting the measuring device.</p>		<p><b>Analogue interface:</b> to connect a suitable peripheral device for analogue processing of the measurements.</p>		<p><b>Mains adapter:</b> 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.</p>
	<p><b>Peak hold function:</b> capturing a peak value within a measuring process.</p>		<p><b>Statistics:</b> using the saved values, the device calculates statistical data, such as average value, standard deviation etc.</p>		<p><b>Power supply:</b> Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request.</p>
	<p><b>Scan mode:</b> continuous capture and display of measurements.</p>		<p><b>PC Software:</b> to transfer the measurements from the device to a PC.</p>		<p><b>Motorised drive:</b> The mechanical movement is carried out by an electric motor.</p>
	<p><b>Push and Pull:</b> the measuring device can capture tension and compression forces.</p>		<p><b>Printer:</b> a printer can be connected to the device to print out the measurements.</p>		<p><b>Motorised drive:</b> The mechanical movement is carried out by a synchronous motor (stepper).</p>
	<p><b>Length measurement:</b> captures the geometric dimensions of a test object or the movement during a test process.</p>		<p><b>GLP/ISO record keeping:</b> of measurements with date, time and serial number. Only with SAUTER printers.</p>		<p><b>Fast-Move:</b> the total length of travel can be covered by a single lever movement.</p>
	<p><b>Focus function:</b> increases the measuring accuracy of a device within a defined measuring range.</p>		<p><b>Measuring units:</b> Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details.</p>		<p><b>DAkkS calibration possible:</b> The time required for DAkkS calibration is shown in days in the pictogram.</p>
	<p><b>Internal memory:</b> to save measurements in the device memory.</p>		<p><b>Measuring with tolerance range (limit-setting function):</b> Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model</p>		<p><b>Factory calibration:</b> The time required for factory calibration is specified in the pictogram.</p>
	<p><b>Data interface RS-232:</b> bidirectional, for connection of printer and PC.</p>		<p><b>ZERO:</b> Resets the display to "0".</p>		<p><b>Package shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.</p>
	<p><b>Data interface USB:</b> To connect the balance to a printer, PC or other peripheral devices.</p>		<p><b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device.</p>		<p><b>Pallet shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.</p>
	<p><b>Data interface Infrared:</b> To transfer data from the balance to a printer, PC or other peripheral devices.</p>				

Your SAUTER specialist dealer: