
# KERN SXS300K-2M







Measuring system	
Adjustment options:	External calibration
Linearity:	50 g   100 g
Readability [d]:	50 g   100 g
Recommended adjusting weight:	300 kg (M1)
Repeatability:	50 g   100 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-300 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	150 kg   300 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Display digit height:	5,100 cm

Technical data about verification		
Minimum load [Min]:	1 kg   2 kg	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	50 g   100 g	

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	10 g
Mininum piece weight at piece counting (Normal):	100 g

Functions	
Counting function:	yes
Data hold function:	yes
Peak function:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service		
Adjustment at the location of insta	allation: 961-249	
DAkkS Certificate:	963-129	
Verification:	965-229	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	915 x 600 x 240 mm
Gross weight:	38 kg
Net weight:	36 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	2,500 m
Dimensions of display device (WxDxH):	232 x 150 x 80 mm
Dimensions of weighing plate (WxDxH):	648 x 502 x 52 mm

## KERN SXS300K-2M



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]

Level indicator:

Material weighing plate:

Revolving screw feet:

Wall mount:

Weighing surface (WxD):

yes

550 x 500 mm

### Piktogramme

#### STANDARD



#### **OPTION**



#### **FACTORY**

