

# KERN WTB 30K-3N



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]



## Measuring system

Adjustment options:	External calibration
Linearity:	10 g
Readability [d]:	5 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5 g
Resolution:	6000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-29,995 kg
Warm up time:	30 min
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	kg

## Display

Additional Display possible:	yes
Display digit height:	2,500 cm

## Functions

Weighing with tolerance range:	yes
--------------------------------	-----

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

## Power supply

Charging time:	12 h
Input voltage:	110 V - 230 V AC
Mains adapter/adaptor included:	CH EURO UK US

n/a:	Mains adapter external
------	------------------------

## Power supply

Operating time (Backlight off):	50 h
Operating time (Backlight on):	30 h
Rechargeable battery:	Rchrg. battery optional - intern

## Service

Adjustment at the location of installation: 961-248

DAkkS Certificate:	963-128
--------------------	---------

## Category

Brand:	KERN
Category:	Balances
Product Group:	Bench scale

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 350 x 200 mm
Gross weight:	4,005 kg
Net weight:	3,115 kg
Shipping method:	Parcel service

## Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	285 x 315 x 128 mm
Dimensions of weighing plate (WxDxH):	260 x 200 x 16,2 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	285 x 315 x 128 mm
Revolving screw feet:	yes
Weighing surface (WxD):	260 x 200 mm

# KERN WTB 30K-3N



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]

## Piktogramme

### STANDARD



### OPTION



### FACTORY

