

## Pro 400 Female Torque Handle (FTH), 14x18 mm, N·m/lbf·ft



Norbar Torque Handles are based on the 'Professional' wrench range and share the same high precision engineering. The Female End versions are either 9 x 12 mm or 14 x 18 mm rectangular type. For many applications a spanner end fitting rather than a socket is the best or, often, the only solution. Typically this will be because the joint is a pipe union (such as a brake pipe).

**Part number:** 15108

**EAN Bar Code:** 5060207564922

**NATO number:** -

**Accuracy:**  $\pm 3\%$

**Operates between:**

**80.00 - 400.00 N·m**

**60.00 - 300.00 lbf·ft**



### TECHNICAL SPECIFICATIONS

- Length: 664 mm
- Weight: 1.69 Kg
- Packed Length: 730 mm
- Packed Weight: 2.44 Kg

### FEATURES

- Factory calibrated to  $\pm 3\%$  and our new mechanism ensures that the accuracy is retained for longer.
- Ergonomic new handle with a high proportion of soft-feel, high grip material.
- Handle material and lens resist all chemicals in common automotive, industrial and aviation use.
- Secure push/pull locking mechanism is quick and intuitive to use and prevents accidental adjustment.
- Large scale window and long scale length for great visibility and accurate setting.
- Unique on a torque wrench, the TimeStrip<sup>®</sup> gives a visual indication that the wrench is due for re-calibration.
- Supplied with a Calibration Certificate, which meets the requirements of ISO 6789-2:2017

NORBAR TORQUE TOOLS LTD. Wildmere Road, Banbury, Oxfordshire,  
OX16 3JU, United Kingdom  
Registered Office as above - Registered in England No. 380480 - VAT No.  
GB 119 1060 05

- Tel: + 44 (0) 1295 270333
- Enquiries: + 44 (0) 1295 753600
- After Sales : + 44 (0) 1295 753635
- Fax: + 44 (0) 1295 753609
- Email: [enquiry@norbar.com](mailto:enquiry@norbar.com)
- Repairs: [repairs@norbar.com](mailto:repairs@norbar.com)