



HHB C Wall Searching Metal Detector SPECIFICATION

- High sensitivity, twin coil induction balance metal detector.
- Dimensions 9cm x 28cm x 3.2cm
- PP3 type battery power source. Low battery indication. Long battery life.
- Normal operating temperature range -9° to +54°C.
- High impact ABS construction. Comfortable to hold and lightweight.
- Audio and visual indication of metal.
- Simple, single control operation. No specialist knowledge required.
- Earphone socket, for use in noisy work situations.

HHB C WALL SEARCHING METAL DETECTOR SPECIFICATION

Product Name	HHB C WALL SEARCHING METAL DETECTOR
Part Numbers	HHB C
Detection Range Guide	<ul style="list-style-type: none"> - 13amp power cable up to 13cm - 15mm copper pipe up to 18cm - Steel reinforcing bar up to 15cm - Cavity wall tie up to 15cm - 30mm iron nail up to 13cm
Dimensions	9cm x 28cm x 3.2cm .
Battery	1 x PP3 (IEC type 6LR61)

Specification subject to change without notice.

C.SCOPE INTERNATIONAL LTD
Kingsnorth Technology Park, Wotton Road, Ashford, Kent TN23 6LN. United Kingdom
Telephone +44(0)1233 629181 Fax +44(0)1233 645897 email info@cscope.co.uk

cscopelocators.com