

MET1000 All in One True RMS Electrical Tester



- LED & LCD Display with self-test
- Detachable Test Probes
- AC/DC Voltage to 1000V
- 200A AC measurement
- True RMS on ACV/ACA
- Inrush Current
- Phase Rotation
- Single pole test
- Data Hold
- Measures voltage without batteries
- Complies with IEC/EN 61243-3:2014
- IP65

DESCRIPTION

The Megger MET1000 is a multifunctional voltage and current tester providing electricians and electrical engineers a versatile and robust hand-held all in one meter, with detachable test leads. Featuring both LED and LCD displays, it gives the user a 200A AC & 1000V AC/DC tester designed for everyday use. CATIV 600V/CATIII 1000V rated, with an IP65 housing for added protection, it reduces the number of testers required in the professional's tool bag.

- Continuity to 50K Ohms
- Auto power On/Off
- 9999 count digital display
- < 0.5s bar response time
- < 0.5s DCV reading response time
- White LED auto backlight display
- Input peak current < 3.5mA @ 1000V
- 39mm width jaw size
- Up to 16mm diameter conductor
- Auto polarity detection
- ELV Indication
- Carrying holster with belt loop
- Hand guard and streamline design
- Ø2mm / Ø4mm tips interchangeable
- LED Torch
- IP65
- CAT IV 600V/CAT III 1000V

MULTIPLE TESTS:

In addition to the versatile auto-ranging voltage and continuity tests the Megger MET1000 has a built-in current clamp for AC current measurement to 200A. With TRMS AC measurements, a phase rotation test and both inrush current and single pole voltage test built in, the MET1000 is a truly versatile electrical tester, ideal for use in commercial, industrial and domestic environments. GS38 shrouds are provided as standard to ensure compliance with the latest standards.

A bright LED torch aids safe working in poorly lit conditions and with the added benefit of an IP65 casing - incorporating a protective finger guard - ergonomic design, instrument carrying holster and a simple to use probe mounting on the rear of tester all help to keep the user safe and the instrument protected.

Incorporating a comprehensive self-test feature, acoustic continuity and voltage indication, a maximum current draw of >3.5mA to avoid unwanted tripping of RCD's/RCBO's and the ability to warn the operator of dangerous voltages, even when the batteries are exhausted, ensure the Megger MET1000 meets the practical demands of today's busy test technicians.

SPECIFICATIONS

(All at 23°C±5°C, ≤ 80% R.H.)

Sampling Rate: 3times/sec
Input peak Current: Is < 3.5mA@1000V

ACA : Ranges 200.0A
 Resolution 0.1A
 Basic Accuracy ±(3.0%+5d) at 45Hz~65Hz

ACV : (w/ batteries) 6.0V~999.9V
 Range: (w/o batteries) 45V~999.9V
 Resolution 0.1V
 Basic Accuracy ±(1.5%+5d) at 45Hz~400Hz

DCV : (w/ batteries) 7.0V~999.9V
 Range: (w/o batteries) 35V~999.9V
 Resolution 0.1V
 Basic Accuracy ±(1.0%+2d)

OHM : Ranges 50KΩ
 Basic Accuracy ±(1.5%+5d)
 Resolution 1Ω

Continuity Beep: <1.8KΩ, 2.7KHz tone buzzer

Rotary Field Indication: Sensitivity 90V to 1000V (Phase to earth)

Frequency Range:45Hz to 65Hz

Single-Pole Phase Check: Sensitivity 90V to 1000V (45Hz – 65Hz Phase to earth)

Dimensions: 57mm(W) x 220mm (L) x 35mm(H)

Weight: (with battery) 200g

Bar Response time: < 0.5s

Reading response time: < 0.5s

Overload Indication: "OL" or "-OL"

Low Battery Indication

Auto Power Off: 30 seconds

Indicator: 2.7kHz Tone Buzzer and ELV LED

Battery Life: (No backlit, Alkaline battery) 1000 operations

Operating Temperature: -15°C~55°C, ≤80% RH

Storage Temperature: -20°C ~ 60°C

Temperature Coefficient: 0.2 x (Spec. Acc)/°C, <18°C or>28°C

Jaw Size: 39mm

Maximum Conductor Size: 16mm

Power Requirement: 2 x AAA Size Battery (R03, LR03, 24D, 24A)

International Standard: IEC/EN 61243-3:2014

Safety Standard: IEC 61010-1, 61010-2-032, EN 61326-1 CAT IV 600V, CAT III 1000V

ORDERING INFORMATION

Description	Part number	Optional Accessories	
MET1000	1013-099	Euro spare metal tips (10 pcs supplied in bag)	2005-269
Included Accessories		UK GS38 spare tips	1013-361
Red and black probe lead set	1013-359	MPU690 proving unit	1001-561
Carry holster with belt loop	1013-360		

SALES OFFICE

Megger Limited
 Archcliffe Road Dover
 CT17 9EN England
 T +44 (0) 1304 502101
 E UKsales@megger.com

MET1000_DS_EN_V0a

www.megger.com
 ISO 9001
 The word 'Megger' is a registered trademark

