

TruCheck 2 Plus, 10 - 350 N·m



TruCheck™ 2 is a cost effective torque wrench checker that has been redesigned to incorporate improved features whilst maintaining ease of use.

The TruCheck™ 2 aims to cut the cost of purchasing a torque wrench checking system and remove the fears over the complexity of using such equipment.

Part number: 43525
EAN Bar Code: -
NATO number: -
Accuracy: -
Operates between:
 10.00 - 350.00 N·m



TECHNICAL SPECIFICATIONS

- Weight: 2.6 Kg
- Accuracy: $\pm 1\%$ torque reading accuracy ($\pm 2\%$ when below 10% of range for the 1,100 N·m TruCheck™ 2 model)
- Display: LCD Display
- Temp Range - Operating: 0°C to $+50^{\circ}\text{C}$
- Temp Range - Storage: -20°C to $+70^{\circ}\text{C}$
- Auto Reset Hold Time: 1,2 or 3 seconds
- Power Consumption: 0.5W
- Electromagnetic Compatibility (EMC) Directive: Designed to comply with EN 61326-1
- Supplied with 27 mm male hexagon plus 3/4" square drive socket
- Requires two Hexagon Socket Head Cap Screws ISO 4762 - M10 - 12.9 to fix in position (not included)
- UKAS accredited calibration is optional
- Environment: IP 40

FEATURES

- Allows torque tool performance to be monitored and tools kept in peak condition.
- Supplied with traceable calibration certificate
- Allows a selection of torque units, three modes of operation (Click, Dial and Track), the ability to store up to 15 targets and select from 12 languages
- Allows operator to set a target value and tolerance
- Inbuilt Micro USB 2.0 port enables power from any USB power source. Plus versions allows for both power and data transfer simultaneously